

HDMI-SP-2

2 Port HDMI Splitter

HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE

Compliant

1.4



Dynamode

How to Connect the HDMI Splitter to your devices?

- Connect the supplied HDMI Cable from the HDMI device into the HDMI Splitter input.
- Connect the cable from your first display (monitor or projector) into the HDMI Out1 slot in the back of the HDMI Splitter.
- Connect the cable from your second display (monitor or projector) into the HDMI Out2 - 8 slot in the back of the HDMI Splitter.
- Connect the optical audio cable from your digital audio receiver into the Optical Out in the back of the HDMI Splitter.
- Plug the 5v wallmount power supply into the wall outlet.

FEATURES

- Splits the HDMI Signal to 2/4/8 HDMI displays
- Maintains 480p, 720p, 720i, and 1080i, 1080p resolutions
- Connects two or more HDMI displays at the same time to the same video source
- Supports HDMI Audio to multiple displays
- Uses HDMI cables to connect to the input and splitter output
- Maintains highest HDMI single link video resolution
- Fully HDMI 1.4 compliant
- Supports HDCP compliant devices
- Extracts digital audio from HDMI input into optical audio output
- Installs in seconds



© 2011 Dynamode
Details correct at going to press. E&OE
All Trademarks Acknowledged